

## CITY OF LACEY Community Development Dept. 420 College Street SE Lacey, WA 98503 (360) 491-5642

## Automatic Sprinkler System Confidence Test Report Addendum

Riser # \_\_\_\_\_

Occupancy Name		Insp. Date	/ /	/	
Occupan	cy Address				
System Type System I.D. # (on riser)					
INSPEC	TOR'S SECTION (All responses reference current inspection)				
1.	GENERAL	YES	NO	N/A	
	a. Are all areas of the building provided with sprinkler protection per NFPA 13?				
	b. Record water pressure at riser				
	c. Record max height of riser (stories OR feet)				
	d. 18 in. min. clearance between the top of the storage & sprinkler deflectors?				
	e. Is all sprinkler piping protected against freezing?				
2.	CONTROL VALVES	YES	NO	N/A	
	Are all control valves in open position & locked or sealed ?				
	b. Are all control valves properly signed?				
3.	WET SYSTEMS	YES	NO	N/A	
	a. Are all cold weather valves in the appropriate open or closed position?	<del></del>			
	b. Is building adequately heated?				
4.	DRY SYSTEMS	YES	NO	N/A	
	a. Is the dry pipe valve in service?	<u> </u>			
	b. Air pressure/priming water level per manufacturer's instructions?				
	c. Were low points drained during this inspection?				
	d. Quick-opening devices operated satisfactory?				
	e. Was dry pipe valve tripped during this inspection? (Attach data)				
	f. Dry-pipe valve room heated properly?  g. Internal exam of piping conducted in (Year) (Required every 5 years)				
	g. Internal or primit or p				
	h. Was the dry-piping checked for proper pitch?	······· ——		-	
5.	ALARMS	YES	NO	N/A	
	a. Did water motor gong test satisfactorily?	<u>-</u>			
	b. Did electric alarm operate satisfactorily?				
	c. Central Station monitoring verified? By whom?				
	d. Water flow alarm activation verified?				
	e. Valve supervision verified?				

6.	SPRI	NKLERS	S						YES	NO	N/A	
	a. Are all sprinklers free from corrosion, loading or obstruction to spray discharge?						_			-		
											-	
		· · · · · · · · · · · · · · · · · · ·										
		d. Does the exterior condition of the sprinkler system appear to be satisfactory?										
	e. Temperature. Are sprinklers proper temperature ratings for their locations?  f. Approximate number of sprinklers in system										-	
g. Date and name of company performing inspection posted on system main valve												
7.	Date	dry-pipe	valve trip tested (con	trol valve partially o	pen). (See Trip	Test Table t	hat follows	.)				
8.	Date dry-pipe valve trip tested (control valve fully open). (See Trip Test Table that follows – do every third year.)											
9.	Date	quick-op	ening device tested.	Required every year.)								
				DRY PIPE OPE	RATING TES	T						
			DRY VALVE				Q	.O.D.		1		
	MAKI	E	MODEL	SERIAL NO.	N	//AKE		MO	DEL	SERIAL NO.		
	TIM	E TO TRIB	P WATER	INITIAL AIR	TDID DOINT	TIME	MATED	AT A	ARM	AT AT	DM	
Q.O.D. TRIP OK	TIME TO TRIP THRU TEST PIPE			PRESSURE			TIME WATER REACHED TEST		ATED	ALARM OPERATED REMOTE		
					PRESSURE	OUTLET		LOCAL				
	MIN.	SEC	C. PSI	PSI	PSI	MIN.	SEC.					
IF NO, EX	PLAIN:				1		1					
11.	List v	vater flov	w tests of main drain i	nade at sprinkler ris	er:							
			Toot Dina	Test Pipe Size					Residual (Flow)			
Date		Test Pipe Location		Pipe Static Pressu		ire Re		esiduai (Flow) Pressure				
		Location	Test	. ipe			Tressure					
									<u> </u>			
12.	Expla	iin any "N	No" answers and com	ments:								
13.	Adju	stments o	or corrections made du	iring this inspection	:							
14.	A lthe	nigh those	a commante ara not th	na regult of an angin	ooring raviaw	the follow	vina doci	rabla im	nrovom	ante ara		
14.		Although these comments are not the result of an engineering review, the following desirable improvements are recommended:										
	recon	nmended	:									
	Sv	stem	$\theta$ is operational	$\theta$ is operat	tional with d	efects	θ	is not c	peratio	onal		
	~ )		T	5 0p w					1			